

DS-2CE56C2T-VFIR3



Key Features

- 1.3 Megapixel high-performance CMOS
- Turbo HD output, up to 720P resolution
- 2.8 – 12mm vari-focal lens
- True Day/Night
- DNR, Smart IR
- Up to 40m IR distance
- IP66 weatherproof

Specification

Model	DS-2CE56C2T-VFIR3
Parameter	720p Vari-focal Turbo HD Turret Camera
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	2.8 - 12 mm @ F1.4
	Angle of view: 80° - 27.2°
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization

Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Turbo HD output
S/N Ratio	More than 52dB
General	
Working Temperature/Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 4.5W
Weather Proof Ratings	IP66
IR Range	Up to 40m
Dimension	Φ130.54 × 102.4mm (Φ5.1" × 4.0")
Weight	565g

Order Model

DS-2CE56C2T-VFIR3

Dimension

